



PRODUCT DATA SHEET

Quality Products and Service Since 1964

GRAPHITE ANTI-SEIZE

Anti-Seize Thread Compound per MIL-PRF-5544 (MIL-T-5544)

PRODUCT DESCRIPTION:

Lub-O-Seal Graphite Anti-Seize is a thread lubricant formulated from 50% petrolatum and 50% graphite powder to meet the requirements of U.S. Military Spec Mil-PRF-5544, MIL-T-5544, SAE-AMS-2518A and A50TF201 specifications. It has excellent conductivity properties allowing for use on spark plug threads exposed to high temperatures. It also offers good lubrication properties for all types of threaded parts and components.

TYPICAL PROPERTIES:

Color:	Black
Appearance:	Smooth paste
Separation:	None
Temp Range:	900 ° F (482 ° C)

APPLICATIONS:

- Spark plug threads
- Knife-type disconnect switches
- Pipe threads
- Nuts, bolts, studs
- Gears, sprockets, chains
- General use anti-seize lubrication

RESTRICTIONS:

As with all petroleum base products, these lubricants should NOT be used in oxygen service.

WARRANTY INFORMATION - PLEASE READ CAREFULLY

Lub-O-Seal Company, Inc. believes that the information in this publication is an accurate description of the typical characteristics and/or uses of the product, but it is your responsibility to thoroughly test the product in your specific application in order to determine its performance, efficacy and safety. Lub-O-Seal specifically disclaims any other expressed or implied warranty, including warranties of merchantability and of fitness for a particular use. Your exclusive remedy and Lub-O-Seal's sole liability for breach of warranty is limited to the refund of the purchase price or the replacement of the product shown to be other as warranted, and Lub-O-Seal expressly disclaims any liability for incidental or consequential damages.

Lub-O-Seal Company, Inc. • 17519 Lewis Drive • Cypress, Texas 77433 - USA

Visit us on the Internet: www.Lub-O-Seal.com