



PRODUCT DATA SHEET


Quality Products and Service Since 1964

LUB-O-GARD™ “L”

Extreme Pressure – Premium Industrial Grease.

PRODUCT DESCRIPTION:

Lub-O-Gard “L” is a red, extreme pressure, premium grease formulated to provide outstanding lubrication and mechanical stability in a wide variety of applications. Lub-O-Gard “L” offers excellent lubrication in both high and low temperature conditions. It contains extreme pressure additives as well as oxidation and corrosion inhibitors for extending equipment life. With the addition of special tackifiers, Lub-O-Gard “L” has excellent adhesion to metal surfaces even when the surfaces have been exposed to oils. Therefore, it offers outstanding resistance to water washout and protects against the harsh effects of outdoor environments. It will provide superior performance under heavy loads and high speeds.

<p>DATA & SPECIFICATIONS:</p> <p>Product Type: Extreme Pressure Grease Product Color: Red Temp Range: 0°F to +500°F Thickener: Bentone Dropping Point: None Sulfur: .3 Max Pumpability: Excellent Shear Stability: Excellent Water Resistance: Excellent Specific Gravity: 1.3 Penetration: 265-290 (worked) NLGI: 2</p>	<p>FOR USE ON:</p> <ul style="list-style-type: none"> • Ball and roller bearings • Electric motors bearings • Wheel and caster bearings • Marine applications • Cams and sleeves • Slides and journals • Multi-temperature applications • Agricultural equipment • Construction equipment • Oil field and well servicing equipment • Industrial machinery • Auto chassis lubrication 
--	---

RESTRICTIONS:

As with all petroleum base products, these lubricants should NOT be used in oxygen service.

WARRANTY INFORMATION - PLEASE READ CAREFULLY

Lub-O-Seal Company, Inc. believes that the information in this publication is an accurate description of the typical characteristics and/or uses of the product, but it is your responsibility to thoroughly test the product in your specific application in order to determine its performance, efficacy and safety. Lub-O-Seal specifically disclaims any other expressed or implied warranty, including warranties of merchantability and of fitness for a particular use. Your exclusive remedy and Lub-O-Seals sole liability for breach of warranty is limited to the refund of the purchase price or the replacement of the product shown to be other as warranted, and Lub-O-Seal expressly disclaims any liability for incidental or consequential damages.

Lub-O-Seal Company, Inc. • 17519 Lewis Drive • Cypress, Texas 77433 - USA
Visit us on the Internet: www.Lub-O-Seal.com