



PRODUCT DATA SHEET

Quality Products and Service Since 1964

LUB-O-GARD™ “MG”

Extreme Pressure – Premium Industrial Grease

PRODUCT DESCRIPTION:


Lub-O-Gard “MG” is a dark gray, extreme pressure, premium grease formulated with a premium base lubricant in addition to molybdenum disulfide (MoS₂) and graphite (two of the finest solid film lubricants known). It also contains rust, oxidation, corrosion inhibitors and extreme pressure additives for extending equipment life and provides outstanding lubrication and mechanical stability in a wide variety of temperatures and applications. Lub-O-Gard “MG” provides superior performance under heavy loads, high speeds, close tolerance applications. It is suited for both high and low temperature applications and provides excellent wear protection and lubrication properties. Lub-O-Gard “MG” is an excellent choice for the high performance lubrication requirements of automotive, heavy equipment and industrial applications.

DATA & SPECIFICATIONS:

Product Type:	Extreme Pressure Grease
Product Color:	Dark Gray
Temp Range:	-10°F to +550°F
Thickener:	Bentone
Dropping Point:	None
Sulfur:	.3 Max
Pumpability:	Excellent
Shear Stability:	Excellent
Water Resistance:	Excellent
Specific Gravity:	1.3
Penetration:	265-290 (worked)
NLGI:	2

FOR USE ON:

- Ball and roller bearings
- Electric motor bearings
- Wheel and caster bearings
- Fifth wheel lubricant
- Chains, gears, sprockets
- Oil field and well servicing equipment
- Industrial machinery
- Heavy equipment lubrication
- Ball and universal joints
- Auto chassis lubrication
- Ovens and kilns
- Press fit assembly



RESTRICTIONS:

As with all petroleum base products, these lubricants should NOT be used in oxygen service.

WARRANTY INFORMATION - PLEASE READ CAREFULLY

Lub-O-Seal Company, Inc. believes that the information in this publication is an accurate description of the typical characteristics and/or uses of the product, but it is your responsibility to thoroughly test the product in your specific application in order to determine its performance, efficacy and safety. Lub-O-Seal specifically disclaims any other expressed or implied warranty, including warranties of merchantability and of fitness for a particular use. Your exclusive remedy and Lub-O-Seals sole liability for breach of warranty is limited to the refund of the purchase price or the replacement of the product shown to be other as warranted, and Lub-O-Seal expressly disclaims any liability for incidental or consequential damages.

Lub-O-Seal Company, Inc. • 17519 Lewis Drive • Cypress, Texas 77433 - USA
Visit us on the Internet: www.Lub-O-Seal.com