



PRODUCT DATA SHEET


Quality Products and Service Since 1964

LUB-O-GARD™ “TFE”

Extreme Pressure – High Performance Industrial Grease with PTFE

PRODUCT DESCRIPTION:

Lub-O-Gard “TFE” is a tan, extreme pressure, high performance grease formulated to provide outstanding lubrication and mechanical stability in a wide variety of applications. Lub-O-Gard “TFE” contains micro-sized PTFE particles combined with extreme pressure additives, rust, oxidation and corrosion inhibitors for extending equipment life. Lub-O-Gard “TFE” offers both high and low temperature performance in addition to excellent wear protection and lubrication properties. These characteristics make it an excellent choice for the high performance lubrication requirements of automotive, heavy equipment and industrial applications.

DATA & SPECIFICATIONS:	FOR USE ON:
Product Type: High Performance Grease	<ul style="list-style-type: none">• Ball and roller bearings• Electric motor bearings• Wheel and caster bearings• Freezers• Heavy equipment lubrication• Motor assembly and break-in• Cams sleeves, journals, slides• Worm gears• Chains, gears, sprockets• Pneumatic equipment• Ball and universal joints• Auto chassis lubrication 
Product Color: Tan	
Temp Range: -5°F to +525°F	
Thickener: Bentone	
Dropping Point: None	
Sulfur: .3 Max	
Pumpability: Excellent	
Shear Stability: Excellent	
Water Resistance: Excellent	
Specific Gravity: 1.3	
Penetration: 265-295 (worked)	
NLGI: 2	

RESTRICTIONS:

As with all petroleum base products, these lubricants should NOT be used in oxygen service.

WARRANTY INFORMATION - PLEASE READ CAREFULLY

Lub-O-Seal Company, Inc. believes that the information in this publication is an accurate description of the typical characteristics and/or uses of the product, but it is your responsibility to thoroughly test the product in your specific application in order to determine its performance, efficacy and safety. Lub-O-Seal specifically disclaims any other expressed or implied warranty, including warranties of merchantability and of fitness for a particular use. Your exclusive remedy and Lub-O-Seal's sole liability for breach of warranty is limited to the refund of the purchase price or the replacement of the product shown to be other as warranted, and Lub-O-Seal expressly disclaims any liability for incidental or consequential damages.

Lub-O-Seal Company, Inc. • 17519 Lewis Drive • Cypress, Texas 77433 - USA
Visit us on the Internet: www.Lub-O-Seal.com