



PRODUCT DATA SHEET

Quality Products and Service Since 1964

MOLY ANTI-SEIZE

Anti-Seize Thread Compound per MIL-PRF-83483 (Mil-T-83483)

PRODUCT DESCRIPTION:

Lub-O-Seal Moly Anti-Seize is a thread lubricant formulated from 50% petrolatum and 50% molybdenum disulfide (MoS₂) to meet the requirements of U.S. Military Spec Mil-PRF-83483 (Mil-T-83483). Good conductivity properties allow for use on spark plug threads exposed to moderate temperatures. It also provides superior lubrication for press fit or close tolerance applications as well as for low speed and heavy load applications. For higher temperature applications, use Lub-O-Seal Graphite Anti-Seize compound designed to meet the higher temperature requirements of Mil-T-5544.

TYPICAL PROPERTIES:

Color:	Black / Gray
Appearance:	Smooth paste
Separation:	None
Temp Range:	750 ° F (398 ° C)

APPLICATIONS:

- Spark plug threads
- Press fit assembly
- Punch or sheer machinery
- Pipe threads
- Nuts, bolts, studs
- Gears, sprockets, chains
- General use anti-seize lubrication

RESTRICTIONS:

As with all petroleum base products, these lubricants should NOT be used in oxygen service.

WARRANTY INFORMATION - PLEASE READ CAREFULLY

Lub-O-Seal Company, Inc. believes that the information in this publication is an accurate description of the typical characteristics and/or uses of the product, but it is your responsibility to thoroughly test the product in your specific application in order to determine its performance, efficacy and safety. Lub-O-Seal specifically disclaims any other expressed or implied warranty, including warranties of merchantability and of fitness for a particular use. Your exclusive remedy and Lub-O-Seal's sole liability for breach of warranty is limited to the refund of the purchase price or the replacement of the product shown to be other as warranted, and Lub-O-Seal expressly disclaims any liability for incidental or consequential damages.

Lub-O-Seal Company, Inc. • 17519 Lewis Drive • Cypress, Texas 77433 - USA
Visit us on the Internet: www.Lub-O-Seal.com