



# PRODUCT DATA SHEET

Quality Products and Service Since 1964

## RED PETROLATUM

Technical Grade Petroleum Jelly (Meets VV-P-236)

### PRODUCT DESCRIPTION:

Lub-O-Seal Red Petrolatum is a multi-purpose lubricant that can be used in a variety of applications. It is designed to meet the requirements of VV-P-236. It is a reddish brown, grease like petroleum jelly that forms a soft, translucent coating which is non-drying and non-hardening.

### TYPICAL PROPERTIES:

Color:	Brownish red to amber tint
Appearance:	Smooth, semi-solid paste
Separation:	None
Melting Point:	135 ° F
Congearing Point:	120 ° F

### APPLICATIONS:

- Corrosion preventative
- General purpose industrial lubricant
- O-ring lubricant
- Used in buffing and polishing compounds
- Wire or cable pulling lubricant

### RESTRICTIONS:

As with all petroleum base products, these lubricants should NOT be used in oxygen service.

#### WARRANTY INFORMATION - PLEASE READ CAREFULLY

Lub-O-Seal Company, Inc. believes that the information in this publication is an accurate description of the typical characteristics and/or uses of the product, but it is your responsibility to thoroughly test the product in your specific application in order to determine its performance, efficacy and safety. Lub-O-Seal specifically disclaims any other expressed or implied warranty, including warranties of merchantability and of fitness for a particular use. Your exclusive remedy and Lub-O-Seal's sole liability for breach of warranty is limited to the refund of the purchase price or the replacement of the product shown to be other as warranted, and Lub-O-Seal expressly disclaims any liability for incidental or consequential damages.

*Lub-O-Seal Company, Inc. • 17519 Lewis Drive • Cypress, Texas 77433 - USA  
Visit us on the Internet: [www.Lub-O-Seal.com](http://www.Lub-O-Seal.com)*