



PRODUCT DATA SHEET

Quality Products and Service Since 1964

PETROLEUM JELLY

White Petrolatum – USP Grade

PRODUCT DESCRIPTION:

Lub-O-Seal Petroleum Jelly is a multi-purpose lubricant that can be used in a variety of applications. It is made from materials that meet USP XXII requirements and FDA requirements as per 21 CFR 172.880. Note: Although all ingredients in this product have FDA compliance, this does not constitute FDA approval. To be approved, the user must also comply with all applicable requirements set forth by the FDA.

TYPICAL PROPERTIES:

Color:	Off-white, yellowish tint
Appearance:	Smooth, semi-solid paste
Separation:	None
Melting Point:	135 ° F
Congeaing Point:	120 ° F

APPLICATIONS:

- Lubricant for pharmaceutical equipment
- O-ring lubricant
- Wire or cable pulling lubricant
- Temporary barrier for paints or stains
- General purpose industrial lubricant

RESTRICTIONS:

As with all petroleum base products, these lubricants should NOT be used in oxygen service.

WARRANTY INFORMATION - PLEASE READ CAREFULLY

Lub-O-Seal Company, Inc. believes that the information in this publication is an accurate description of the typical characteristics and/or uses of the product, but it is your responsibility to thoroughly test the product in your specific application in order to determine its performance, efficacy and safety. Lub-O-Seal specifically disclaims any other expressed or implied warranty, including warranties of merchantability and of fitness for a particular use. Your exclusive remedy and Lub-O-Seal's sole liability for breach of warranty is limited to the refund of the purchase price or the replacement of the product shown to be other as warranted, and Lub-O-Seal expressly disclaims any liability for incidental or consequential damages.

*Lub-O-Seal Company, Inc. • 17519 Lewis Drive • Cypress, Texas 77433 - USA
Visit us on the Internet: www.Lub-O-Seal.com*