



CLEAR-TITE CONTACT CEMENT

Clear-Tite is a special adhesive that was developed to hold fast at temperatures of up to 250° F. It's the clear choice for installations where a hot pan, a warm oven, or a steamy faucet might cause lesser glues to soften.



Clear-Tite Contact Cement has been a leading adhesive for more than 40 years for everything from tile and linoleum to glass and carpeting. It is widely used in the manufacture and installation of kitchen cabinets, countertops, desktops, tabletops, store fixtures, and hard orthotics. It leaves your installation flawless - even when the heat is on.

PROVIDES A HIGH-STRENGTH BOND RESISTANT TO LIQUIDS AND HEAT

REPAIRS SEAT COVERS, WEATHER STRIPPING AND LOOSE FLOORING

SETS ON CONTACT TO ELIMINATE THE NEED FOR CLAMPING

BONDS PLASTIC LAMINATES AND WOOD VENEERS



FEATURED APPLICATIONS

Clear-Tite works across many applications including:



KITCHEN
CABINETS



COUNTER
TOPS



STORE
FIXTURES



HARD
ORTHOTICS

ABOUT RH ADHESIVES

We make cements for bonding and repairing specialized materials. Our unique products have stood the test of time because they are the best at what they do.

AMERICAN MADE SINCE 1949



PHYSICAL PROPERTIES

BASE	Neoprene Resin
SOLVENTS	Heptane, Acetone, Toluene, MEK
COLOR	Beige
VOC CONTENT	420 g/L
VISCOSITY	Low, 750-900 cps at room temperature
APPLICATION	Brush, Roller, Notched Trowel, Squeeze Bottle
SOLIDS	21% ± 1% (approx.)
NET WEIGHT	7.2 lbs./gallon (approx.)
SERVICE TEMPERATURE RANGE	-30° to 250° F
FLASH POINT	17° F

See Safety Data Sheet (SDS) for additional information.



rhadhesives.com
sales@rhadhesives.com
Tel. 978-897-8000

@therightglue

/rhadhesives